



FINAL BUILD SPECIFICATION

Production Number:

18270

Report		Date
Order Date		5/26/2017
Preliminary	163/1065	5/26/2017
Build Specification Agree	163/1063	7/14/2017
Price Agree	166/1065	8/1/2017
Final	170/1066	8/25/2017
Production		
Invoice		
LAST EDIT	170/1066	8/25/2017

Chassis Year: 2017
Chassis: Ford Type III, 158"WB, 100"
V.I.N.:
Chassis Source: Horton
HEV Model: 553B
Type: 3
Series: 100
Module Num:
HEV S/N:

Department: Elsinboro Fire Company
Address: 35 Delaware Avenue
Post Office:
City: Salem
State: NJ **Zip Code:** 08079
Contact: Sherry Biddle, EMS Captain
Previous Production Num:

Dealer: VCI EMERGENCY VEHICLE SPECIALISTS
Sales Person: DIGANGI, DAVE
Project Developer: JOHN COX

Projected Dealer Price:

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification
				OK NOT OK

AB Horton Emergency Vehicles Feature List

AC CHASSIS

AFE 1 1 FORD E-SERIES CHASSIS

AFE46016 0 1 CHASSIS, 2016 FORD E-450 SUPER DUTY, 158" CUTAWAY-GAS

The chassis required to complete the ambulance conversion shall be supplied by Horton.

8/22/2017 !!! CHASSIS A 2017 MODEL YEAR ILO 2016 WILL BE DEALER SUPPLIED PER MIKE HARPER'S E-MAIL OF 7/27/2017.
!!! VCI STOCK CHASSIS AT HEVC, 1FDXE4FS2HDC05545

AJNSPIC0 1 1 CHASSIS INTERIOR COLOR SHALL BE GRAY

B CHASSIS MODIFICATIONS, HARDWARE AND ACCESSORIES

BH02A310 1 1 STAINLESS STEEL WHEEL COVERS

Stainless steel wheel covers shall be installed.

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
BH03A000	1	0	MUD FLAPS: front Install rubber mud flaps behind each front tire. 11/10/2016	DELETE	—
BH03B000	1	1	MUD FLAPS: rear Install individual rear mud flaps behind each set of rear wheels.	—	—
BH070000	1	1	REINFORCE REAR BUMPER END CAPS Reinforce end caps of rear bumper for greater impact resistance. 11/11/2016	—	—
BH08A000	0	1	RUNNING BOARDS: ALD Install heavy duty aluminum diamond plate running boards and splash shields. 11/10/2016	—	—
BH110000	1	1	REAR STEP/ BUMPER ASSEMBLY The center section of the rear step bumper shall be constructed of aluminum grip strut and be hinged to assist in patient handling.	—	—
BH160000	1	0	REAR AIR BAGS FOR TYPE III CHASSIS Rear suspension to have air bag stabilizer kits with left and right fillers. Locate air fills in the curbside rear compartment. 11/10/2016	DELETE	—
BH170000	1	0	FRONT AIR BAGS Front suspension to have air bag stabilizers with left and right fillers. Locate air filler under the front bumper. 11/10/2016	DELETE	—
BL070000	1	1	BATTERIES, STANDARD ON TYPE III CHASSIS (2) batteries shall be installed in the specified battery compartment on a pull out tray.	—	—
BL26B000	1	1	BACKUP ALARM RESET Backup alarm to automatically reset to on if alarm was manually canceled using the control panel alarm cut-off switch (FL25) during previous use.	—	—
BL26I000	0	1	CAMERA SYSTEM FOR USE WITH I4g A camera system shall be installed as noted below. The system is to use the i4G front screen as its monitor. 11/11/2016 QUANTITY: 1 LOCATE: REAR OF MODULE (BACK-UP) NOTE: REQUIRES SELECTION OF OPTION PAL00006 NOTE: A MAXIMUM OF FOUR (4) CAMERA CAN BE USED IN THIS SYSTEM. NOTE: SELECTION OF AN I4G GPS SYSTEM REDUCES THE NUMBER OF AVAILABLE CAMERA INPUTS TO THREE.	—	—

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK

BL32A000	1	1	OEM AM/FM/CD PLAYER SHALL BE PROVIDED BY THE OEM MANUFACTURER OEM AM/FM/CD player shall be provided by the OEM manufacturer on all Horton supplied chassis.	___	___
----------	---	---	---	-----	-----

11/11/2016

C	CONVERSIONS
----------	--------------------

CA575000	0	1	CONVERSION MODEL: 553B Type III SUPER DUTY E-450: MINIMUM BODY DIMENSIONS: (Exterior) -Height: 89" -Width: 96" -Length: 169" (Interior) -Height: 72" -Aisle 20" -Width: 20" (from edge of cot in wall position to squad bench riser) -Length: 165" OVERALL DIMENSIONS (Including Chassis, Module and Step): -Height: 112" (to top of vent) -Width: 100" -Length: 269.5"	___	___
----------	---	---	--	-----	-----

CA575001	1	1	553B STREETSIDE FORWARD: Clear Door Opening: 18.2" wide x 79.1" high Actual Dimension: 22.0" wide x 82.1" high x 20.3" This area shall be accessed through a single outside hinged door. The compartment shall house the vehicle's primary O2 cylinder. The compartment shall be vented to the outside.	___	___
----------	---	---	--	-----	-----

CA575001 TN01E000	0	1	OXYGEN BOTTLE BRACKET: Zico OTS electric Electric operated oxygen bottle mount for cylinder loading and securing. Controls to be mounted on the in side of the compartment door.	___	___
----------------------	---	---	--	-----	-----

11/11/2016 BOTTLE SIZE: "H"

CA575002	1	1	553B STREETSIDE INTERMEDIATE: Clear Door Opening: 49.2" wide x 38.3" high Actual Dimension: 51.5" wide x 41.5" high x 20.3" This area shall be accessed through double, outside hinged doors. Both doors shall have exterior door handles and latching devices.	___	___
----------	---	---	--	-----	-----

8/25/2017 NOTE: INSTALL AN ELONGATED HOLE IN THE LOWER LEFT CORNER FOR WIRE ACCESS TO COMPARTMENT.

!!! INSTALL ALL ADD-ON ELECTRICAL COMPONENTS ON LEFT WALL UNDER INVERTED HOPS SENSOR. (EXCEPT PD BOX WHICH WILL BE LOCATED BEHIND DRIVERS SEAT)
!!! THE STANDARD COMPARTMENT HEIGHT IS INCREASED 2" TO ACCOMMODATE THE NEW CPR SEAT HIP CUSHION HEIGHT REQUIREMENT
!!! STORE STAIR CHAIR IN LOWER SECTION OF COMPARTMENT ON IT'S SIDE.

CA575002 DR09LB00	0	1	SHELF FOR LED LIGHTED DOUBLE DOOR COMPARTMENT A diamond plate adjustable shelf shall be installed in the area listed below.	___	___
----------------------	---	---	---	-----	-----

8/25/2017 LOCATE: BOTTOM OF INSIDE/OUTSIDE ACCESS IN INTERMEDIATE COMPARTMENT

!!! SHELF TO BE USE WITH I/O

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
CA575002	0	1	EXPANDED METAL CAGE FOR PROTECTION OF EQUIPMENT	—	—
DR11CA00			Install an expanded metal cage around the onboard electrical equipment per location noted below. Include access ports to equipment with grip lock around the edges of the openings.		
8/21/2017			LOCATE: LEFT WALL BELOW THE INVERTED HOPS SENSOR		
CA575004	1	1	553B STREETSIDE REAR:	—	—
			Clear Door Opening: 32.0" wide x 38.3" high		
			Actual Dimension: 37.4" wide x 41.5" high x 20.3"		
			This area shall be accessed through double, outside hinged doors.		
			Both doors shall have exterior door handles and latching devices.		
7/17/2017			NOTE: 2" INCREASE IN HEIGHT		
CA575004	0	1	SHELF FOR LED LIGHTED VERTICAL COMPARTMENT	—	—
DR08L000			A diamond plate adjustable shelf shall be installed in the following location.		
8/24/2017			LOCATE: CENTERED		
			!!! NOTCH SHELF FOR THE CLOSE-OUT LEFT SIDE BACK WALL		
CA575004	0	1	CLOSEOUT, EXTERIOR COMPARTMENT	—	—
DR11CL00			Install a closeout to block off exterior access to the exterior compartment as noted below. Fabricate closeout to match compartment material.		
8/24/2017			LOCATE: LEFT SIDE BACK WALL TO COVER RECESSED BOARD STORAGE ON MAIN WALL.		
CA575005	1	1	553B CURBSIDE REAR:	—	—
			Clear Door Opening: 22.1" wide x 79.1" high		
			Actual Dimension: 26.2" wide x 82.1" high x 20.3"		
			This area shall be accessed through a single outside hinged door.		
8/1/2017					
CA575005	0	3	SHELF FOR LED LIGHTED VERTICAL COMPARTMENT	—	—
DR08L000			A diamond plate adjustable shelf shall be installed in the following location.		
7/17/2017			LOCATE: RIGHT SIDE OF DIVIDER		
			!!! INSTALL FULL HEIGHT SHELF TRACK SO SHELVES CAN BE POSITIONED AND USED AT STREET LEVEL.		
			!!! BOTTOM OF SHELF IS TO BE 42" FROM FLOOR, SPACE OTHERS (2) EVENLY ABOVE RIGHT SIDE OF DIVIDERS FOR USE WITH I/O		
CA575005	0	1	DIVIDER FIXED, VERTICAL COMPARTMENT	—	—
DR11A000			Install a 16" deep fixed vertical divider shall be installed in the location listed below. (Divider material is to match the compartment material)		
8/1/2017			LOCATE: 12.00" FROM RIGHT WALL		
CA575005	0	1	ROK BACKBOARD STRAP	—	—
DR12A000			Install a ROK backboard strap in the designated backboard compartment.		
7/13/2017			LOCATE: BETWEEN LEFT COMPARTMENT WALL AND LEFT SIDE DIVIDER TO RETAIN BACKBOARDS		

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK

CA575006	1	1	553B CURB SIDE, FRONT:	___	___
			Clear Door Opening: upper 22.1" wide x 65.0" high lower 22.1" wide x 12.6" high Actual Dimension: upper 27.2" wide x 65.0" high x 28.5" deep lower 27.2" wide x 12.6" high x 20.3" deep This area shall be accessed through two outside hinged doors and from an opening located on the curb side forward wall. The upper area shall be primarily used for storage of customer furnished jump kits, the lower area for the storage for two batteries on a roll out tray.		
CAB93AF0	0	1	KKK-A-1822F CERTIFICATION LABEL	___	___
			The vehicle shall have weight/payload, electrical load and KKK-A-1822F certification stickers installed in the O2 compartment.		

11/10/2016

CB	BODY MODIFICATIONS/OPTIONS
-----------	-----------------------------------

CB06SW00	0	1	DOUBLE STEP CURBSIDE ENTRY, 3"	___	___
			The curbside skirt, forward of the rear wheel well shall be dropped 3 inches. Two integral ALD steps within the side patient door step well shall be available upon opening the side door for easier and lower access to the patient compartment.		
CB07E000	0	1	COT MOUNT REINFORCEMENT PLATES: Power Load	___	___
			Additional under floor reinforcement is required for future installation of a Stryker Power Load system.		
CB09SA00	1	1	PATIENT AREA SOUND PROOFING/ACOUSTIC ENHANCEMENT PACKAGE	___	___
			Install standard sound control package.		
CB09SB00	0	1	WALK THROUGH MODIFICATION FOR CUSTOM HEAT/AC SYSTEM	___	___
			Shift the bulkhead walk through opening 2" toward the curbside of vehicle so it is compatible with the custom heat/ac unit.		
CBSP0001	0	1	SPECIAL INSTRUCTION, BODY MODIFICATIONS	___	___
			!!! REDUCE SIDE ENTRY DOOR 2" DO TO GLOVE BOXES OVER DOOR.		

11/10/2016

8/1/2017

8/1/2017

8/24/2017 !!! REDUCE SIDE ENTRY DOOR 2" DO TO GLOVE BOXES OVER DOOR.

D	MODULE BODY HARDWARE
----------	-----------------------------

CG050000	1	0	WINDOWS, REAR MODULE BODY ENTRY DOORS	___	___
			The rear module entry doors shall have solid windows. The side entry door shall have a sliding window.		

DELETE

11/10/2016

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
DG060000	1	0	WINDOW, SLIDING FOR SIDE ENTRY DOOR The side entry door shall have a sliding window. 11/10/2016	DELETE	—
DG06A000	1	0	WINDOW, CURBSIDE OF BODY ABOVE SQUAD BENCH A fixed window shall be installed on the curbside of the body above the squad bench. 11/10/2016	DELETE	—
DG06D000	0	1	ELECTRONIC PRIVACY WINDOWS IN PATIENT DOORS: The patient area door windows shall include liquid crystal privacy control. When privacy is needed, a switch shall be activated to turn the windows solid so they cannot be seen through even at a very close distance. The windows shall return to clear with a second touch of the switch. All door windows to have fixed glass. The switches shall be labeled "PRIVACY". 7/13/2017 SWITCH LOCATION: FULL HEIGHT BOLSTER NEAR SIDE ENTRY DOOR & REAR CONTROL PANEL IN INHALATION AREA	—	—
DG080000	1	1	EMERGENCY DOOR RELEASE MECHANISM, REAR DOORS Install standard emergency release knobs on top and bottom of rear module entrance doors.	—	—
DG08A000	1	1	DOOR HANDLES Install Tri-Mark free floating style door handles with pre-stretched stainless steel cables. Include three piece interior door panels on all access doors.	—	—
DH000000	1	1	Vi-Tech body mounts Install standard Vi-Tech body mounts.	—	—
DH03B000	1	1	MIRROR STAINLESS STEEL SPLASH SHIELDS Install #8 mirror stainless splash shields on the lower front face of the body just behind the cab access doors. These splash shields are to be the same height as the diamond plate front corner guards. 11/11/2016	—	—
DH040000	1	1	MODULE BODY FENDERS: stainless steel Rear wheel housings shall have stainless steel flare skirts to protect the wheel house opening and side body finish.	—	—
DH04RP00	1	1	POLISHED STAINLESS LOWER BODY RUB RAILS Polished stainless lower body rub rails, with #8 mirror finish, are to be along the bottom of the body on each side.	—	—
DH330000	1	1	REAR DOOR HOLD OPENS, GRABBER Install chrome Cast Products "Grabber" style rear door hold opens. (NOTE: HOLD OPENS MUST BE RELOCATED IF TELESCOPIC LIGHTS ARE ORDERED)	—	—

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
DL480000	0	1	ELECTRIC DOOR LOCKS: compartment Install power activated door locks on all exterior compartment doors. Locks to be activated by a switch at each patient area access door. Locks may be overridden by a door key. A separate lock switch will be located in the front radio console if option DL48D000 (wired to OEM locks) is not selected. 11/11/2016	—	—
DL48A000	1	1	ELECTRIC DOOR LOCKS: access doors Install power activated door locks on all patient area access doors. Locks to be activated by a switch at each patient area door, and controlled with the access door locks. Locks may be overridden by a manual slide lever or by the door key. A separate lock switch will be located in the front radio console if option DL48D000 (wired to OEM locks) is not selected.	—	—
DL48B000	0	1	ELECTRIC DOOR SWITCH: concealed Install a concealed switch on the exterior of the vehicle to operate the power door lock circuit. Doors shall be wired to unlock only on this circuit. 11/29/2016 LOCATE: CHASSIS GRILLE AREA	—	—
DL48D000	0	1	ELECTRIC DOOR LOCKS WIRED TO OEM SWITCHES The module door locks and compartment locks (if ordered) are to be wired to the chassis door lock switches. 11/10/2016	—	—
DLH40000	0	1	RECESSED LICENSE PLATE BRACKET A Cast Products #LP0002 recessed license plate bracket shall be installed per the attached drawing. The bracket will include lighting in the top to illuminate the license plate. 11/29/2016 !!! CENTER IN REAR RISER.	—	—
DM100000	1	1	REFLECTORS: All patient compartment entry doors shall have red reflectors in the lower corner.	—	—
DR220000	1	1	RUBBER MATTING IN EXTERIOR COMPARTMENTS Ribbed rubber matting will be installed on the floor and shelves of all exterior compartments.	—	—
DR23A000	1	1	RUBBER COVERED WALLS IN BACKBOARD COMPARTMENT The interior of the backboard compartment is to be covered with rubber matting to protect equipment stored in this area. 7/19/2017 COLOR: GRAY (CURBSIDE REAR)	—	—

E	PAINT AND STRIPING
----------	---------------------------

ED010000	1	0	CHASSIS PAINT: standard white	DELETE	—	—
			Chassis color to be standard white. 11/10/2016			

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
ED020000	0	1	CHASSIS PAINT: other color Paint CHASSIS special color 11/11/2016 PAINT COLOR: BLACK OVER RED PAINT NUMBER: TO BE DETERMINED	—	—
ED040000	1	0	MODULE PAINT: standard white Paint module standard white Sikkens #FLNA4002. 11/10/2016	—	—
				DELETE	
ED050000	0	1	MODULE PAINT: other color Paint MODULE special color 11/11/2016 PAINT COLOR: BLACK OVER RED PAINT NUMBER: TO BE DETERMINED	—	—
ED060000	0	1	STRIPE: bottom half Paint bottom half special color 8/1/2017 PAINT COLOR: BLACK OVER RED PAINT NUMBER: TO BE DETERMINED	—	—
ED090000	0	1	STRIPE: custom Special paint stripe See drawing 8/21/2017 !!! PAINT THE MODULE ROOF AND UPPER MODULE SIDES BLACK 13.00" BELOW THE BOTTOM OF THE DRIP RAIL EDGE. !!! ANGLE THE UPPER BLACK DOWN TO THE LOWER WINDOW LEVEL OF THE CAB. !!! PAINT THE CAB ROOF BLACK DOWN TO THE BOTTOM OF THE WINDOW. !!! PAINT THE HOOD BLACK. !!! FOLLOW THE STRIPING AROUND THE REAR OF MODULE !!! HORTON QUOTE #52417SW-3.	—	—
ED20AA00	1	0	STRIPE: 8" Scotchlite beltline Apply an 8" Scotchlite beltline stripe in the color listed below: 11/11/2016	—	—
				DELETE	
ED20PS00	1	1	PAINT PANEL: sample A painted test panel shall be prepared with the following paint color and number, to confirm correct paint selection. The panel will be mailed as designated. 8/22/2017 PAINT COLOR: BLACK PAINT NUMBER: FLNA4145 PAINT COLOR: RED PAINT NUMBER: HORTON 129 !!! PAINT SAMPLE SENT TO DAVID DIGANGI ON 08/11/2017 !!! RED PAINT SAMPLE (HORTON 129) NOT APPROVED 8/17/2017 !!! RED PAINT SAMPLES - FLNA3050&FLNA3051 SENT TO DAVID DIGANGI ON 8/22/2017	—	—
ED300000	1	0	PIN STRIPE: 1/4" black The single color stripe as described above shall include a 1/4"black pinstripe that surrounds the entire accent stripe. 8/21/2017	—	—
				DELETE	

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK

F	INTERIOR CABINET DOORS, HANDLES & HARDWARE
----------	---

FE010000	1	1	FULL HEIGHT PULL HANDLES ON SLIDING PLEXIGLAS DOORS	___	___
			All sliding cabinet doors to have full length pull handles.		

FE01FT00	1	1	LATCH, HINGED DOOR: Southco flush stainless steel pull style	___	___
			Install stainless flush mount Southco pull latches on the hinged interior cabinet doors.		

FE02A000	1	1	PLEXIGLAS COLOR: light tint	___	___
			All Plexiglas doors to be light tint.		

FE060000	1	0	STAINLESS STEEL COUNTER TOPS (STANDARD)	___	___
			Stainless steel pan formed counter tops shall be installed in the patient area.		

DELETE

8/23/2017

FE06F000	0	2	SOLID SURFACE COUNTER TOP WITH COVED INTERIOR EDGES	___	___
			Asolid surface counter top shall be installed made from the material listed below. The inside vertical and horizontal shall have a smooth rounded radius instead of a 90 degree mated surface. Counter is to include radiused and tapered corners.		

8/23/2017 COLOR: GREY GRANITE

FE08ST00	1	1	INHALATION PANEL (STANDARD):	___	___
			The inhalation panel is to be fabricated from composite material and covered with Formica to match to color selected.		

FE08SV00	0	1	INHALATION PANEL CLOSEOUT	___	___
			Install a D/A finsihed aluminum close-out on the bottom of the inhalation panel. Panel includes a hinge-down door to access the O2 bypass valves.		

5/25/2017

G	INTERIOR COLORS, UPHOLSTERY AND SEATING
----------	--

GF01R000	0	1	INTERIOR COLOR SCHEME: Custom	___	___
			Interior colors are as follows:		

8/23/2017 FLOOR: LONPLATE BLACK 163
RISER: WILSONART FASHION GRAY

WALL: WILSONART FASHION GRAY
CABINET: WILSONART FASHION GRAY

UPHOLSTERY: FLINT GRAY
COUNTERTOP: GREY GRANITE

ACCENT STRIPE: WILSONART BLACK 1595 (NO ACCENT STRIPE ON REAR DOORS)

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
GF02M000	1	1	INSIDE CABINET FINISH: paint The interior of all aluminum cabinets shall have a durable paint finish. The painted surface shall be washable and non-absorbent. See the appropriate Interior Color Scheme option for paint color information.	—	—
GF02P000	1	1	RISERS: The interior of this vehicle is to contain no wood or wood products. The risers are to be made of reinforced structural composite board covered with Formica per the color description. Formica will not be installed on the risers if stainless steel riser options are selected.	—	—
11/11/2016					
GK120000	1	0	BOXED ATTENDANT SEAT	—	—
				DELETE	
A boxed seat base shall be located at the head of the cot. The base shall be fabricated from aluminum. The seat shall have a 3" thick padded seat cushion and a 3" thick Lumbar contoured backrest.				—	—
11/10/2016					
GK12A300	0	1	HIGH BACK ATTENDANT SEAT WITH CHILD SAFETY, 4PT Delete the boxed in attendant seat cushions. Install a USSC high back bucket seat with integral 4pt seatbelt and child safety seat. The seat to be adjustable front to rear.	—	—
11/10/2016					
GK12B100	0	1	SWIVEL MOUNT BASE FOR HIGH BACK ATTENDANT SEAT A Bostrom high back attendant seat will be mounted on a Bostrom #10001975 swivel seat base. This option will require the vehicle heat/ac system to be relocated into the bottom of the linen cabinet. Note: Not available with HOPS system.	—	—
8/22/2017 NOTE: ATTENDANT SEAT MUST SWIVEL 360 DEGREES					
GK150000	5	4	SEAT BELTS: Install standard 4pt seatbelts per quantity and locations selected.	—	—
11/11/2016 LOCATE AS FOLLOWS: HEAD OF BENCH MIDDLE OF BENCH FOOT OF BENCH CPR SEAT					

H	INTERIOR CABINETRY, STREET SIDE
----------	--

HK000000	1	0	LINEN CLOSET	—	—
				DELETE	
Install a vertical storage cabinet behind the attendant seat. The upper storage area shall house the primary electrical distribution area. The lower section shall be used for miscellaneous storage. Each area shall be accessed through hinged doors. The electrical distribution area shall include a Southco key lock/latching device. The entire cabinet shall be fabricated from aluminum and shall then be painted, unless otherwise specified.				—	—
8/1/2017					

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
HK000200	0	1	LINEN CLOSET WITH HEAT/AC UNIT IN BOTTOM A vertical storage cabinet shall be located behind the attendant seat. The upper storage area shall house the primary electrical distribution area. The lower section shall be used to house the vehicle heat/ac unit. The outer surface of this area will be covered with perforated stainless steel providing intake air to the heat/ac unit. The center section can be utilized for miscellaneous storage. The electrical distribution area and the center storage area shall be accessed through hinged doors. The electrical distribution area shall include a Southco key lock/latching device. The entire cabinet shall be fabricated from aluminum and shall then be painted, unless otherwise specified.	—	—
8/1/2017 OPTION #CB09SB00 MUST ALSO BE SELECTED WHEN THIS OPTION IS USED.					
THE PASS THOROUGH WINDOW MUST BE RELOCATED IN THE BODY IN TYPE 1 VEHICLES.					
HK001000	1	1	HOPS SYSTEM: The unit is to be equipped with the HOPS system.	—	—
8/1/2017 NOTE: AIR BAG IN THE ATTENDANCE SEAT AREA WILL BE DELETED DO TO SWIVEL BASE CONFIGURATION					
HK001B00	1	1	RADIUS STYLE CABINET TRIM Install smooth 1.5" radiused trim on all applicable interior cabinets.	—	—
HK01A000	1	0	STREETSIDE WALL WITHOUT CPR SEAT Street side cabinet wall to be per drawing. All cabinets over 14"H will include (1) standard adjustable shelf.	—	—
11/10/2016 Note: This option deletes the tubular air bag for the CPR seat.					
HK01B000	1	1	STREETSIDE WALL WITH CPR SEAT Street side wall to have CPR configuration. All cabinets over 14"H will include (1) standard adjustable shelf. SEE DRAWINGS	—	—
11/11/2016					
HK01D000	0	2	ADJUSTABLE VERTICAL DIVIDERS: Install adjustable shelf tracks recessed into the upper and lower interior cabinet walls. Fabricate Plexiglas dividers to fit vertically into the cabinet and between the recessed tracks. The dividers shall be adjustable within the track.	—	—
8/1/2017 LOCATE: INHALATION CABINET QUANTITY: (6) ABOVE AND (6) BELOW FIXED CENTER SHELF					
HK17C000	1	0	SHARPES/WASTE DISPOSAL: Install sharpes and waste disposal in a metal container recessed into the inhalation counter top. Access to the waste receptacle shall be through a spring loaded door. The neck of the sharps container shall protrude through the top surface of the receptacle. Disposal of both containers shall be accessible by raising a hinged aluminum lid.	—	—
11/10/2016					

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK

HSP00001 0 1 SPECIAL INSTRUCTION, STREETSIDE CABINETRY

8/21/2017 !!! INSTALL I/O FORWARD END OF MAIN WALL BELOW THE INHALATION AREA UNDER COUNTER TOP.
 !!! INSTALL A SLIDING PLEXIGLAS INSIDE/OUTSIDE ACCESS TO THE STREET SIDE INTERMEDIATE COMPARTMENT AS DESCRIBED.
 !!! WIDTH IS TO BE DETERMINED BY THE LOCATION OF EXTERIOR ELECTRONICS, ROLL OVER SENSOR AND DIVIDER. THE HEIGHT SHALL BE 14.00".

I	INTERIOR CABINETS AND SQUAD BENCH, CURB SIDE
---	---

IA200000 1 1 SQUAD BENCH STORAGE:

Storage shall be provided under the bench cushions. The area shall run where possible under the bench. The storage pan shall be fabricated from aluminum and shall be accessed by raising the split cushions.

IG070110 1 1 SQUAD BENCH END RESTRAINT FOR USE WITH HOPS

Install a restraint that is 16" above the seating surface at the head end of the bench. Standard for use in conjunction with HOPPS 3-point seat belts.

8/22/2017

IG10A000 1 1 BENCH HOLD OPENS: gas

Install gas spring hold opens on squad bench lid.

IG10Q000 1 1 BENCH HOLD-DOWN: paddle latches (Pair)

Install recessed paddle latches into the squad bench riser to retain the squad bench lids in the closed position. The latches shall be both passive and positive.

IG15A000 1 1 BENCH CUSHION EDGE TRIM:

Trim bench cushion edge with protective aluminum trim, to protect horizontal edge of squad bench cushion from tears..

IG15B000 1 1 BENCH BACK CUSHION: full size

Delete individual squad bench back cushions. Install full size cushion.

IK17E000 0 1 SHARPS/WASTE STORAGE IN A PULL OUT DRAWER IN SQUAD BENCH

Install a drawer in the face of the squad bench in the specific location noted below. This drawer will house both sharps and waste containers.

8/22/2017 LOCATE:

FORWARD OF SQUAD BENCH

!!! INSTALL WASTE ONLY IN BENCH RISER BELOW FORWARD BENCH SEAT PER DRAWING.

IK18AA00 1 1 CURBSIDE OVERHEAD CABINET: hinged doors

Storage shall be provided above the squad bench. The storage shall run the full length of the squad bench and shall be accessed through hinged Plexiglas doors that are held in the open position with gas activated rods. The entire cabinet shall be fabricated from aluminum. The cabinet is to be 9" H to meet current K requirements.

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK

IK18BD00	0	2	ADJUSTABLE VERTICAL DIVIDERS: Install adjustable shelf tracks recessed into the upper and lower cabinet walls. Fabricate Plexiglas dividers to fit vertically into the cabinet and between the recessed tracks. The dividers shall be adjustable within the track and held into position with cushioned track shelf supports.	—	—
----------	---	---	---	---	---

8/1/2017

IK280000	0	1	PASS THROUGH ACCESS TO THE CURBSIDE REAR COMPARTMENT Inside/outside access to the curbside rear compartment shall be provided as described. Width is to be determined by the location of any exterior divider and the height shall start 41" from the exterior compartment floor to interior closeout unless noted otherwise below.	—	—
----------	---	---	---	---	---

8/1/2017 *SIZE: MATCH DIVIDER SPACING*

DOOR STYLE: HINGED PLEXIGLAS

NOTE: SIZE PER DIVIDER/SHELF LOCATION

IK29A000	0	1	GLOVE STORAGE ABOVE SIDE ENTRY DOOR Install recessed storage above the side access door for two (2) boxes of gloves. Provide oval openings in a hinged padded and upholstered door for glove access.	—	—
----------	---	---	--	---	---

Note: Reduce the height of the front wall cabinet 1.00" to accommodate this option.

8/22/2017 *GLOVE BOX SIZE: (2) 10.5"W X 5"H X 4"D*

J	INTERIOR CABINETS, FRONT
----------	---------------------------------

JAK03000	1	1	FRONT WALL CABINET: The front wall cabinet shall be arranged per drawing. Additional configuration information may follow.	—	—
----------	---	---	--	---	---

8/25/2017 *CABINET WALL FINISH: FASHION GRAY PAINT*

JAK03G00	0	1	GLOVE STORAGE ABOVE FRONT WALL CABINET Storage for (2) glove boxes shall be provided in the header above the front wall cabinet. The face of the storage area will be covered in matching interior vinyl and include openings for access to each storage area. The header will be hinged for restocking or removal of glove boxes.	—	—
----------	---	---	--	---	---

8/25/2017 *NOTE: REDUCE THE STANDARD CABINET HEIGHT 1" FOR THIS OPTION.*

GLOVE BOX SIZE: (2) 10"W X 5"H X 4"D

!!! RIGHT SIDE OF GLOVE BOX DOOR TO BE FIXED FOR CLEARANCE OF GLOVE BOX ABOVE SIDE ENTRY

JE040000	4	4	FRONT WALL DOORS: Plexiglas Front cabinet wall to have hinged Plexiglas doors, and latch type as designated.	—	—
----------	---	---	--	---	---

11/11/2016 *TYPE: PLEXIGLAS*
LATCH STYLE: SOUTHCO

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
JK130000	1	1	CAB TO MODULE WALKTHROUGH DOOR, HINGED Install a recessed hinged front cabin closeout door on the right front compartment wall.	—	—
K MODULE INTERIOR ACCESSORIES AND TRIM					
KG02B000	2	2	IV HANGER, CAST PRODUCTS WITH RUBBER ARM Cast products recessed IV hangers with rubber arms for attaching solution bags shall be installed in the designated locations. 11/14/2016 LOCATE: MID SECTION OF COT, CENTER POSITION MID SECTION OF SQUAD BENCH	—	—
KG09B000	1	1	CEILING GRAB RAIL: standard (2) 2ft rails or (1) 6ft rail anti-microbial Cabinet wall "A" will have (1) 6' rail over cot as standard. Cabinet wall "B" will have (2) 2' rails, 1-forward and 1-to rear of CPR seat.	—	—
KG09D000	0	1	GRAB RAIL: additional 6ft with anti-microbial coating Additional (6)ft long ceiling mounted stainless steel grab rail with anti-microbial coating. 11/29/2016 LOCATE: ASILE EDGE OF SQUAD BENCH	—	—
KG09K000	1	1	PATIENT DOOR GRAB RAILS: angled with anti-microbial coating All patient access doors to have heavy duty angled stainless steel grab rails with smooth radius corners and flange mounting and anti-microbial coating.	—	—
KG110000	1	1	FLOOR TRIM Trim floor with cove molding at non rolled areas of floor.	—	—
KG120000	1	1	CABINET TRIM Trim all vertical and horizontal edges.	—	—
KG16B000	1	1	CEILING MATERIAL, PLATINUM WHITE ALUMINUM COMPOSITE The standard module ceiling material shall be platinum white aluminum composite.	—	—
KG17A000	2	2	FIRE EXTINGUISHERS: 5lb ABC Supply five pound fire ABC extinguisher(s). Ship loose, or identify mounting location(s). 11/14/2016 LOCATE: SHIP LOOSE FOR DEALER INSTALLATION	—	SHIP LOOSE

L	COT MOUNTS AND ACCESSORIES
----------	-----------------------------------

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK

~~LG03G000~~ 1 0 ~~STAT TRAC:~~ **DELETE** — —

The Ferno Washington Stat Trac system shall be installed.

Note: This option complies with GSA change notice 8.

11/14/2016

LSP00001 0 1 **SPECIAL INSTRUCTIONS, COT MOUNTS & PATIENT HANDLING** — —

CUSTOMER SUPPLIED

8/1/2017 !!! INSTALL THE STRYKER FLOOR PLATE ASSEMBLY KIT ONLY FOR THE POWER-LOAD COT RETENTION SYSTEM TO BE KKK-A-1822F COMPLIANT. DEALER TO INSTALL THE REMAINDER OF THE CUSTOMER SUPPLIED POWER-LOAD SYSTEM.

M **LIGHTBARS FRONT AND REAR** **DELETE**

11/10/2016

~~MAM148F0~~ 1 0 ~~FRONT LIGHTBARS FOR 96" BODIES~~ **DELETE** — —

11/10/2016

~~MAM148R0~~ 1 0 ~~REAR LIGHTBARS FOR 96" BODIES~~ **DELETE** — —

11/10/2016

MM ELECTRICAL EMERGENCY VISUAL WARNING SYSTEMS

MM030000 1 1 **WHELEN M SERIES LIGHTING OPTIONS:** — —

MM030000 0 1 **M6 SERIES LED, AMBER** — —

MM06A000 Whelen M6 series L.E.D. lights shall be installed in the designated locations.

7/13/2017 LOCATION: (1) CENTERED OVER REAR DOORS

LENS COLOR: CLEAR

MM030000 0 2 **M7 SERIES LED, RED** — —

MM07R000 Whelen M7 series L.E.D. lights shall be installed in the designated locations.

7/13/2017 LOCATION: FRONT INTERSECTION

LENS COLOR: CLEAR

MM030000 0 1 **M7 SERIES LED, WHITE WITH CLEAR LENS** — —

MM07W000 Whelen M7 series L.E.D. lights shall be installed in the designated locations.

11/14/2016 LOCATION: FRONT UPPER CENTER "KKK" POSITION

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
MM030000	0	12	M9 SERIES LED, RED	—	—
MM09R000			Whelen M9 series L.E.D. lights shall be installed in the designated locations.		
11/29/2016			LOCATION: (4) FRONT OF MODULE, SPACED EVENLY (LIGHT BAR ALTERNATIVE) (2) STREET SIDE (2) CURBSIDE (2) REAR OF MODULE, UPPER CORNERS (2) REAR OF MODULE, WINDOW LEVEL		
			LENS COLOR: CLEAR		
MM10CL00	0	5	L.E.D. WARNING: compartment door SINGLE COLOR (EACH)	—	—
			Install custom made L.E.D. light strips on the interior of the exterior compartment door panels. The light strips shall have an integral lens strip for maximum light disbursement. Installation will be flush with the ALD inner panel. The light strip shall flash when the compartment door is open, and the red flashing light circuit is activated.		
7/17/2017			COMPARTMENT: ALL REAR FACING COMPARTMENTS COLOR: AMBER		
			!!! PROGRAM TO TRIPLE FLASH.		
			!!! EXCLUDING BATTERY COMPARTMENT DOOR		
MM120000	1	0	TECNIQ LIGHTING OPTIONS:	DELETE	—
11/10/2016					
MM26A000	8	0	RED HALOGEN FLASHING LIGHTS, 900 SERIES	DELETE	—
			Whelen 900 series halogen flashing lights with chrome flange shall be installed in each upper corner of the module side and front face.		
11/14/2016					
MM26K000	1	0	WHITE HALOGEN KKK FRONT LIGHT, 700 SERIES	DELETE	—
			(1) clear flashing series 700 light to be mounted centered on front face of modular body.		
11/10/2016					
MM26Q000	1	0	AMBER HALOGEN KKK REAR LIGHT, 700 SERIES	DELETE	—
			(1) amber flashing 700 series halogen light to be mounted centered on rear of modular body over rear doors.		
11/10/2016					
MM26S000	1	0	INTERSECTION LIGHTS, 700 SERIES HALOGEN	DELETE	—
			Front fender intersection lights shall be Whelen 700 series halogen.		
11/14/2016					
MM26TT00	1	1	GRILLE LIGHTS, 500 SERIES SUPER LED's TIR6	—	—
			TIR6, 500 series Super LED grille lights shall be installed.		
11/14/2016			LENS COLOR: CLEAR		

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
MM26TT10	1	1	GRILLE LIGHT HOUSINGS FOR 500 SERIES TIR6 LED GRILLE LIGHTS LH52603/04 grille light housings will be installed on the cross member of the grille for mounting of 500 series Super LED, TIR6 grille lights.	___	___
MM700000	0	1	FLASHING SEQUENCE FOR LED LIGHTING Specify flash pattern programming for selected or all applicable warning lights: 11/14/2016 LIGHTS: ALL FLASH PATTERN: ACTION SCAN	___	___
MN AUDIBLE EMERGENCY WARNING SYSTEMS					

MN35C000	1	1	SIREN: SS700 Specified siren to be: Signal Vehicle Products Model SS700	___	___
MN40A000	1	1	SIREN INSTALL: The siren listed above shall be supplied and mounted as defined. 8/22/2017 !!! INSTALL SIREN BETWEEN CUP HOLDERS ON CONSOLE	___	___
MN45BA00	1	1	SIREN SPEAKERS, C.P. 3801 FOR FORD E SERIES Cast Products #SAD3801-08E35-1 & #SAP3801-08E35-1 siren speakers will be install in each outboard end of the chassis bumper.	___	___
MN50A000	1	1	SPEAKER INSTALL: bumper Speaker Selections (Bumper Installed)	___	___
O LIGHTS					

OL09F000	1	0	KKK SIDE BODY MARKER LIGHTS, 700 SERIES HALOGEN (PAIR) DELETE Install Whelen 700 series turn/marker lights on each rear side of the module body. Lights provide module body night time side lighting visibility and turning signal indication. 11/10/2016	___	___
OL09M000	0	1	KKK SIDE BODY MARKER LIGHTS, M6 SERIES L.E.D. (PAIR) Install red Whelen L.E.D. M6 series turn/marker lights on each rear side of the module body. Lights provide module body night time side lighting visibility and turning signal indication. 11/10/2016	___	___
OL34L000	1	1	LED EXTERIOR COMPARTMENT LIGHTING All exterior compartments will be lighted with LED strip lighting. A vertical strip will be installed inside both sides of each compartment. The lights shall be directed toward the back of the compartment. 11/14/2016	___	___

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
OL35D000	1	1	ROLLED ICC MARKER LIGHTS Install standard rolled marker lights along the upper corner post front and rear. 11/14/2016	—	—
OM25A000	2	0	SIDE SCENE LIGHTS, 900 SERIES Install Whelen 900 series 13 degree angled side scene lights. 11/14/2016	—	—
			DELETE		
OM25CW0	0	4	M9 SERIES LED SCENE LIGHT Install Whelen M9 series LED side scene lights. 11/14/2016 LOCATE: (2) STREET SIDE (2) CURBSIDE	—	—
OM25D000	2	0	LOAD LIGHTS WHELEN 900 SERIES Rear load lights to be (2) Whelen 900 series 26 degree angled scene lights. 11/14/2016	—	—
			DELETE		
OM25FB90	0	2	LOADING LIGHT, WHELEN M9 SERIES, LED Install Whelen M9 Series LED loading light with chrome flange. 7/13/2017 LOCATION: ABOVE REAR ENTRY DOORS	—	—
OM30A000	1	0	TAIL LIGHTS, 600 SERIES HALOGEN Install Whelen 600 series halogen stop/tail, turn, and reverse lights. 11/14/2016	—	—
			DELETE		
OM30D000	0	1	TAIL LIGHTS, M6 SERIES Whelen M6 series brake/tail, amber arrow turn and backup lights to be installed in the selected location. 11/14/2016 LOCATE: STACKED ABOVE REAR RISER	—	—

P	ELECTRICAL POWER GROUP
----------	-------------------------------

PAL00006	1	1	INTELLIPIX i4G: Install the Intelliplex i4G electrical system. System is to include a USB port installed under the dash for ease of programming. 11/29/2016 !!! NOTE UPPER STREET SIDE WIRING HARNESS TO DROP BELOW THE 20.00" DEEP CPR BOARD CABINET LOCATED ABOVE THE CPR SEAT.	—	—
PAL00A00	0	1	MODULE DISCONNECT DEFAULT The module disconnect circuit shall default to the "on" position when the battery switch is activated. 11/14/2016	—	—

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
PAL01B00	1	1	BATTERY SWITCH: std. operation The "Master" battery switch shall switch battery power "on" and "off" to the ambulance body and conversion added electrical circuits only. All OEM chassis electric's, (headlights, ignition, keep alive) shall remain wired "hot" and have no ability to be switched "off", and provide circuit function as provided by the chassis manufacturer. NOTE: DO NOT MODIFY OEM BATTERY SWITCH UNLESS STATED BELOW.	—	—
PAL02000	1	0	INVERTER PREWIRE OPTIONS: 11/29/2016	DELETED	—
PAL02200	1	0	INVERTER INSTALL OPTIONS: 11/10/2016	DELETED	—
PAL04C00	1	1	CHARGER/POWER SUPPLY: 45 AMP Install a 45 amp battery conditioner in the designated electrical equipment area. Conditioner to be wired to the batteries through the standard shoreline inlet. WEIGHT	—	—
PAL30A00	2	2	110V INTERIOR OUTLET Two 110V interior outlets are provided as standard on all models. The standard locations are in the inhalation area and the wall over the squad bench. List the standard outlet locations and any deviation from the standard, plus any additional outlet locations below: 11/14/2016 LOCATE: INHALATION AREA LOCATE: FRONT WALL CABINET	—	—
PAL31C00	3	3	INTERIOR 12VDC OUTLETS: cigarette lighter type 12 volt outlets to use cigarette lighter style connectors. 8/25/2017 LOCATE: INHALATION AREA (2) LOCATE: FRONT WALL CABINET CONFIGURE: BATTERY HOT NOTE: INSTALL USB/12V OUTLETS	—	—
PAL38A00	1	0	SHORELINE: twist lock Mount standard 3 terminal 20 amp twist lock shoreline outlet: 11/29/2016	DELETED	—
PAL38E00	0	1	SHORELINE, KUSSMAUL SUPER AUTO EJECT, 20 AMP NON ARCING Install a 20 amp Kusssmaul non-arcing auto ejection shoreline receptacle. 11/29/2016 LOCATE: STREET SIDE OF MODULE BODY	—	—
PAL40000	1	0	EXTRA 12VDC CIRCUIT BREAKER: An extra circuit breaker shall be installed. 11/10/2016	DELETED	—

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
PL10A000	1	1	SWITCH PANEL MOUNT: Switch panel to be flush mounted in upper face of console.	—	—
PL11F000	1	1	PROGRAMMING: AUDIBLE LOW VOLTAGE ALARM Program an audible alarm to activate if the voltage drops below 11.8 volts for 120 seconds.	—	—
PL11G000	1	1	LIGHT PROGRAMMING: park brake A warning shall display on the front console readout, advising to set the Parking Brake, should the modular disconnect switch be "ON" and the transmission placed in "PARK" or "NEUTRAL". It will also advise to Disengage the Parking Brake should the vehicle be placed into gear. 11/14/2016 CONFIGURE: WIRE ALARM TO ACTIVATE WITH RED FLASHER CIRCUIT	—	—
PL19A000	1	1	REPORT LIGHT Install a 12" Tecniq LED bar style report light.	—	—
PL22C000	1	1	STEP WELL LIGHT: Install a 10.5" LED Vista light strip in the standard location on the bench side of the step well. Light to activate with door open.	—	—
PL27C000	7	7	PATIENT CEILING DOME LIGHTS: WELDON Rear patient compartment lights to be Weldon halogen lamps and to be operated by individual cot and bench switches. Lamps to be infinitely adjustable and come on with the doors open. 11/14/2016 LOCATE: 3 OVER STREET SIDE OF COT 3 OVER CURBSIDE OF COT 1 WALK/PASS THROUGH	—	—
PSP00001	0	1	SPECIAL INSTRUCTION, ELECTRICAL POWER, PROGRAMMING 8/1/2017 !!! SUPPLY & INSTALL (2) USB DUAL PORT 4.2 AMP OUTLETS, MODEL #091-219-4. LOCATE: (2) CONSOLE	—	—
Q	HEATING, AIR CONDITIONING AND INTERIOR ENVIRONMENT				

QH291000	0	1	CABINET MOUNTED HEAT/AC UNIT FOR SWIVEL ATTENDANT SEAT The vehicle heat/ac unit will be installed in the bottom of the linen cabinet instead of the attendant seat base. Requires vertical mounting of a custom combo unit. Unit will use (1) #10008973, 3-ply filter. 11/11/2016	—	—
QH29E100	1	0	HEAT/AC SYSTEM FORD E SERIES CHASSIS Install a ProAir Pre-charged 12V heat/AC system below the attendant seat. Unit is to include a replaceable carbon filter at the air intake point. 8/1/2017	—	—

DELETE

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK

~~QL43N000~~ 1 0 ~~NFPA COMPLIANT VENTING-CAST VENTS~~ **DELETE** — —
 Install an NFPA style venting system to include a 400cfm exhaust vent along with a static vent. Install 9.5" square polished covers on both vents per drawings.

11/11/2016

QL43P000 0 1 **NFPA COMPLIANT VENTING-CAST PAINTED** — —
 Install an NFPA style venting system to include a 400cfm exhaust vent along with a static vent. Install 9.5" square cast covers on both vents per drawings. Covers to be painted body color.

11/11/2016

R	CAB CONSOLE AND COMMUNICATIONS
----------	---------------------------------------

RJ01A000 1 1 **ANTENNA COAX 1:** — —
 An RG 58U coax shall be installed so that the ambulance conversion need not be disassembled.

7/12/2017 *EXTERIOR TERMINATION: CENTERED ON MODULE ROOF*

INTERIOR TERMINATION: BEHIND DRIVER'S SEAT

RJ01B000 0 1 **ANTENNA COAX 2:** — —
 Install additional antenna coax and accesses.

8/22/2017 *EXTERIOR TERMINATION: CENTER OF MODULE ROOF*

INTERIOR TERMINATION: FRONT CONSOLE

RJ03MM00 0 1 **ANTENNA: K-94 mount.** — —
 Supply and install K-94 antenna base as designated. This option is less the antenna coax. An antenna coax option must be selected to be installed.

8/22/2017 *COAX NUMBER(S): ANTENNA COAX 1
 ANTENNA COAX 2*

!!! 3/8 NMO ILO K-94 FOR ALL ANTENNAS

~~RJ040000~~ 1 0 ~~RADIO CABLE PULL WIRE~~ **DELETE** — —
 A standard pull wire for radio installation shall be installed from behind the driver's seat to behind the inhalation panel.

8/22/2017

~~RJ05A000~~ 1 0 ~~FRONT CONSOLE:~~ **DELETE** — —
 A console shall be fabricated to match the OEM dashboard material, color and texture. Room shall be provided on the face of the console for installation of radio and siren controls.

11/14/2016

RJ05A200 0 1 **CONSOLE, CARPET COVERED FABRICATED ALUMINUM WITH MAP STORAGE** — —
 The cab console shall be constructed from aluminum and covered with gray polyurethane elastomeric coating. The console shall provide installation space for radio heads in addition to the standard electrical control panel and siren. The rear section of the console will have three front to rear storage sections for maps, books etc.

8/22/2017 *!!! INSTALL VCI STYLE CONSOLE.*

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK
RJ05CP00	0	1	CUP HOLDERS Install two (2) cup holders recessed into the console per drawing. 11/14/2016 <i>SIZE: TWO TIER</i>	—	—
RJ080000	1	0	RADIO POWER/GROUND: Install 6 gauge cable to positive and ground studs for radio power. 7/19/2017	—	—
			DELETE		
RJ08A000	0	2	RADIO POWER/GROUND: Install three 6 gauge cables to positive and ground studs for radio power. Wire one constant hot, one ignition hot and one ground. 8/25/2017 <i>LOCATE: (1) INSIDE CAB CONSOLE</i> <i>(1) BEHIND DRIVER'S SEAT - ADD REMOVABLE COVER</i> <i>!!! CONFIGURE BATTERY SWITCHED (10 WIRE), BATTERY HOT 165 WIRE), AND GROUND.</i>	—	—
T OXYGEN AND SUCTION					
TN002000	1	0	OXYGEN BOTTLE MOUNT, VERTICAL TRACK FOR QRM-V Vertical track for mounting of a QRM-V O2 bottle mount shall be welded on the back wall of the compartment in the right hand corner. The O2 bottle mount is adjustable for "M" or "H" size tanks. 11/10/2016	—	—
			DELETE		
TN01MW00	1	0	OXYGEN BOTTLE, CYLINDER BRACKET: Zico Zico QRM-V oxygen bracket shall be installed. 11/14/2016	—	—
			DELETE		
TN020000	0	1	OXYGEN ACCESS: A clear Plexiglas door shall be provided in the patient area wall for access to the oxygen cylinder valve. The door shall be hinged so that it swings into the oxygen cylinder storage compartment. The opening shall be trimmed with anodized aluminum edging. O.D. dimension of the access is 7" wide x 11" high. 11/14/2016	—	—
TN030000	2	2	OXYGEN OUTLETS, STANDARD Two oxygen outlets to be provided as standard and located in the inhalation panel unless relocated per option TN03RL00.	—	—
TN03A000	0	1	OXYGEN OUTLET: additional Install additional oxygen outlet(s). 8/22/2017 <i>LOCATE: FORWARD END OF CURBSIDE OVERHEAD CABINET</i>	—	—
TN04A000	1	1	ADAPTER TYPE: Ohio Diamond II Oxygen outlets to be Ohio Diamond II.	—	—

OptionNum	Std	Qty	Header/Description/Data/Comment	Final Build Specification	
				OK	NOT OK

TN050000	1	0	FLOWMETER:	DELETE	—	—
			Supply dial type flowmeter.			

11/10/2016

TN060000	1	1	OXYGEN WRENCH:		—	—
			Install oxygen wrench in oxygen compartment. Mount secure so not left hanging. Mount with length of chain or cable so not removable.			

TN08B100	0	2	D BOTTLE MOUNT: QR-D-2 SINGLE, STRAPLESS		—	—
			Install a Zico QR-D-2 Quic-release strapless d-cylinder oxygen bracket.			

8/22/2017 LOCATE: RIGHT SIDE BOTTOM OF LINEN CABINET

!!! RAISE SHELVES IF NECESSARY.

TN100000	1	0	VACUUM OUTLET: inhalation wall	DELETE	—	—
			A single vacuum panel shall be installed in the inhalation area. The outlet shall be of the same style as the oxygen system and hooked to the onboard vacuum pump.			

11/10/2016

TN11B000	1	1	ASPIRATOR: SSCOR		—	—
			Install an SSCOR aspirator. The system shall include a #22000 wall mounted regulator, and a #23002 canister holder. Plumb to the pump selected.			

TN12D000	1	1	VACUUM PUMP:		—	—
			Install a CAPL #D34 SE (T282) 12vdc electric suction pump.			

U	LETTERING
----------	------------------

UP020000	0	1	LETTERING:		—	—
			No lettering included.			

5/25/2017

UP180000	1	1	DOOR REFLECTORS		—	—
			Install 2" x 12" strips of red Scotchlite at the top of each entry door placed horizontally.			

V	CHANGE ORDERS
----------	----------------------

Z04	0	1	Fuel, Tags, Etc.		—	—
			Allowance for fuel, tags and administrative.			